

Dual Screen LCD Console Drawers

Optimize rack space. Maximize rack monitoring


DVI-D-USB & VGA-USB , Audio , Hub

Features

- 2U 17.3 inch widescreen Dual LCD Console Drawer
- Dual DVI & VGA Port
- 1920 x 1200 native WUXGA Ultra high resolution
- Support FHD with 1080p resolution.
- Front 1xUSB, Rear 2xUSB 2.0 Type A, Sharing USB peripheral Device for computer (ex, flash disk, hard driver, KB/Mouse)
- 104-key keyboard with touch pad mouse.
- USB 2.0 Keyboard & Mouse
- Self-locking and auto release rails for ultra convenience.
- Build in 2x 2 watts speakers

Option

- Composite Video input
- HDMI or Display Port input
- 3G / HD / SD –SDI Broadcast grade input
- 48V, 24V or 12V DC Power



Rear of KVM-1701W-D2




| Part No. | | KVM-1701W-D2 |
|--|--|--|
| No. of ports | | 1 |
| KVM Connectors | | 2 x DVI-D & 2x VGA / 1 x USB |
| LCD | Size | Dual 17.3 inch FULL HD display |
| | Backlight | LED |
| | Resolution | 1920*1080 (support resolution up to 1920*1200) |
| | Max.color | 262K |
| | Luminance | 300 cd/m2 |
| | View Angel (H/V) | 140 / 120 |
| | Contrast Ratio | 650 : 1 |
| Port Selection | | N/A |
| USB HUB | | Yes , Front x1 & Rear x 2 USB 2.0 Type A for USB Peripheral Device |
| Audio | | 1 x 3.5mm Audio jack |
| KB/Mouse Emulation | | USB 2.0 |
| Rack Depth (rack cabinet front rails to rear rails) | | 600mm to 1100mm |
| Power | | 100-240V AC 50/60Hz via IEC Type power cord |
| Environment | | Operation temp: 0 to 50 °C Storage temp: -20 to 60 °C Humidity: 10% - 90%, non-condensing Shock: 10G acceleration (11ms duration) Vibration: 17 to 500Hz 1G PTP |
| Physical Dimensions (W x H x D) / Net Weights (KGs) | | 443x63x580mm / 14.5 |
| Packing Dimensions (W x H x D) / Gross weights (KGs) | | 735x590x215mm / 19.0 |
| Accessory | | |
| KVM-1701W-D2 | 1.8meter IEC Type Power Cord x1 , 1.8meter DVI Cable x2 , 1.8meter VGA Cable x2 , 1.8meter USB Cable x1 ,1.8meter Audio Cable x1 | |

Dual Screen LCD Console Drawers


Optimize rack space. Maximize rack monitoring
DVI-D-USB & VGA-USB , Audio , Hub

Display present on different resolution

Resolution 1920 x 1200



Resolution 1920 x 1080



Resolution 1600 x 1200

