

Combo DB15 LCD Console Drawers

Optimize rack space. Maximize rack monitoring
Waterproof Version



The Anso range of LCD console drawers provides a variety of features that simplify to access servers to making system monitoring, troubleshooting and software upgrades.

The self-locking rails when in the fully extended open position and the ultra-convenient auto lock release when the LCD panel is closed, make for simple and hassle free operation.

Available with 17" A-Grade LCD panels, combo DB15 single, 8 or 16 port integrated KVM switch.

LCD module front face compliant with IP65 waterproof grade, keyboard and touch pad module IP68 grade for tough environment application.

Features

- Support combo interface, VGA-USB & VGA-PS2. (single port VGA-USB)
- Short depth design suit for mobile rack and limited space.
- LCD front face IP65 waterproof grade.
- Silicon 98-key keyboard and touch pad IP68 waterproof grade.
- Quick and simple installation.
- Self-locking and auto release rails for ultra-convenience.
- Port selection via push buttons or On-Screen-Display (OSD).
- Dedicated daisy chain port to expand up to 240 servers.



Rear of KVM-1701S-AST-M2-IP



Rear of KVM-1708S-AST-M2-IP



Rear of KVM-1716S-AST-M2-IP

Part No.		KVM-1701S-AST-M2-IP	KVM-1708S-AST-M2-IP	KVM-1716S-AST-M2-IP
Direct no. of Computers		1	8	16
Maximum no. of Computers		1	232(Daisy Chain)	240(Daisy chain)
LCD	Size	17"		
	Backlight	LED		
	Resolution	1280*1024		
	Max.color	16.7M		
	Luminance	250cd/m2		
	View Angel (H/V)	176 / 170		
Contrast Ratio		1000 : 1		
Port Selection		N/A	Push Button, OSD or Hotkey	
USB Local console / Expansion Slot		N/A		
KB/Mouse Emulation		USB	USB & PS2	
Rack Depth		380mm to 620mm (rack cabinet front rails to rear rails)		
Power		100-240V AC 50/60Hz via IEC Type power cord		
Environment		Operation temp: 0 to 50°C Storage temp: -20 to 60°C Humidity: 10% - 90%, non-condensing Shock: 10G acceleration (11ms duration) Vibration: 17 to 500Hz 1G PTP		
Physical Dimensions / Net Weights		443x42x457.2mm (WxHxD) /14KG		
Packing Dimensions / Gross weights		605x168x700mm (WxHxD) /17KG		
Accessory				
1.8meter IEC Type Power Cord (1.8meter VGA & USB A Type Cable for KVM-1701S-AST-M2-IP)				
Option Relate Item				
CVU-018	1.8meter 2-in-1 KVM Cable-USB&VGA	CVP-018	1.8meter 3-in-1 KVM Cable-PS/2&VGA	
CVU-030	3.0meter 2-in-1 KVM Cable-USB&VGA	CVP-030	3.0meter 3-in-1 KVM Cable-PS/2&VGA	
CVU-050	5.0meter 2-in-1 KVM Cable-USB&VGA	CVP-050	5.0meter 3-in-1 KVM Cable-PS/2&VGA	