

Combo CAT6 LCD Console Drawers

Optimize rack space. Maximize rack monitoring




Features

The AnnsO range of LCD console drawers provides a variety of features that simplify to access servers to making system monitoring, troubleshooting and software upgrades. The self-locking rails when in the fully extended open position and the ultra convenient auto lock release when the LCD panel is closed, make for simple and hassle free operation. Available with 17" or 19" A-Grade LCD panels, Combo CAT6 8, 16 or 32 port integrated KVM switch & additional one USB local console. Using CAT5 or CAT6 ethernet cable, support max. Computer distance up to 40 meters away.


- Support combo interface, VGA-USB & VGA-PS/2.
- Additional one USB Local console to add local KB/Mouse & VGA.
- Up to 40 meters between Servers to KVM.
- Durable 104-key keyboard and touch pad.
- Quick and simple installation.
- Self-locking and auto release rails for ultra convenience.
- Port selection via push buttons or On-Screen-Display (OSD).
- Dedicated daisy chain port to expand up to 256 servers.



Rear of KVM-1708/1908ASL-M2/ULC



Rear of KVM-1716/1916ASL-M2/ULC



Rear of KVM-1732/1932ASL-M2/ULC

| Part No. | KVM-1708ASL-M2/ULC | KVM-1716ASL-M2/ULC | KVM-1732ASL-M2/ULC | KVM-1908ASL-M2/ULC | KVM-1916ASL-M2/ULC | KVM-1932ASL-M2/ULC |
|------------------------------------|--|--------------------|--------------------|--------------------------------|--------------------|--------------------|
| Direct no. of Computers | 8 | 16 | 32 | 8 | 16 | 32 |
| Maximum no. of Computers | 232(Daisy Chain) | 240(Daisy chain) | 256(Daisy chain) | 232(Daisy Chain) | 240(Daisy chain) | 256(Daisy chain) |
| LCD | Size | 17" | | 19" | | |
| | Backlight | LED | | LED | | |
| | Resolution | 1280*1024 | | 1280*1024 | | |
| | Max. color | 16.7M | | 16.7M | | |
| | Luminance | 250cd/m2 | | 250cd/m2 | | |
| | View Angel (H/V) | 176 / 170 | | 170 / 160 | | |
| Contrast Ratio | 1000 : 1 | | 1000 : 1 | | | |
| Port Selection | Push Button, OSD or Hotkey | | | | | |
| USB Local console | Yes , USB x2 for KB/ Mouse , VGA x1 | | | | | |
| Max. Computer Distance | 40 meters (Servers to KVM) | | | | | |
| KB/Mouse Emulation | USB & PS2 | | | | | |
| Rack Depth | 500mm to 1100mm (rack cabinet front rails to rear rails) | | | | | |
| Power | 100-240V AC 50/60Hz via IEC Type power cord | | | | | |
| Environment | Operation temp: 0 to 50°C Storage temp: -20 to 60°C Humidity: 10% - 90%, non-condensing Shock: 10G acceleration (11ms duration) Vibration: 17 to 500Hz 1G PTP | | | | | |
| Physical Dimensions / Net Weights | 448x42x580mm (WxHxD) / 12.0KG | | | 448x42x580mm (WxHxD) / 12.5KG | | |
| Packing Dimensions / Gross weights | 715x140x780mm (WxHxD) / 18.0KG | | | 715x140x780mm (WxHxD) / 18.5KG | | |
| Accessory | | | | | | |
| 1.8meter IEC Type Power Cord | | | | | | |
| Option Relate Item | | | | | | |
| DGU | CAT6 KVM Dongle-USB&VGA | | DGP | CAT6 KVM Dongle -PS/2&VGA | | |
| DGD | CAT6 KVM Dongle-USB&DVI | | | | | |