


# USB HUB DB15 LCD Console Drawers

Optimize rack space. Maximize rack monitoring



 (USB Port for device access)

The Annsor range of LCD console drawers provides a variety of features that simplify to access servers to making system monitoring, troubleshooting and software upgrades.


The self-locking rails when in the fully extended open position and the ultra-convenient auto lock release when the LCD panel is closed, make for simple and hassle free operation.

Available with 17" or 19" A-Grade LCD panels, combo DB15 8 or 16 port integrated KVM switch & with an option remote IP console.

Support USB HUB 2.0 and touch screen enable function.



Rear of KVM-1708P/1908P-AST-M7



Rear of KVM-1716P/1916P-AST-M7

## Optional Remote IP Access

- An expansion slot allows you to add an optional KVM over IP module to enable remote access to your servers.
- Gain BIOS level access to your servers for system maintenance, support or failure recovery via secure SSL authentication and encryption.



## Features

- Support USB interface, VGA-USB.
- Front 1x USB, Rear 2x USB 2.0 Type A, Sharing USB peripheral Device for computer ( ex, flash disk ,hard driver, KB/Mouse ).
- Durable 104-key keyboard and touch pad.
- Quick and simple installation.
- Self-locking and auto release rails for ultra-convenience.
- Port selection via push buttons or On-Screen-Display (OSD).
- Access Control List (ACL) security function for up to 8 independent user accounts.

Part No.	KVM-1708P-AST-M7	KVM-1716P-AST-M7	KVM-1908P-AST-M7	KVM-1916P-AST-M7
Direct no. of Computers	8	16	8	16
Maximum no. of Computers	8	16	8	16
LCD	Size	17"	19"	
	Backlight	LED	LED	
	Resolution	1280*1024	1280*1024	
	Max. color	16.7M	16.7M	
	Luminance	250cd/m2	250cd/m2	
	View Angel (H/V)	176 / 170	170 / 160	
	Contrast Ratio	1000 : 1	1000 : 1	
Port Selection	Push Button, OSD or Hotkey		Push Button, OSD or Hotkey	
Expansion Slot	Option for remote IP access		Option for remote IP access	
USB HUB	Yes, Front 1x USB 2.0 , Rear 2x USB 2.0 Type A for USB Peripheral Device			
Touch Screen	Yes, for option ( Driver needed )			
KB/Mouse Emulation	USB			
Rack Depth	500mm to 1100mm ( rack cabinet front rails to rear rails )			
Power	100-240V AC 50/60Hz via IEC Type power cord			
Environment	Operation temp: 0 to 50°C Storage temp: -20 to 60°C Humidity: 10% - 90%, non-condensing Shock: 10G acceleration ( 11ms duration) Vibration: 17 to 500Hz 1G PTP			
Physical Dimensions / Net Weights	448x42x600mm (WxHxD) / 12.5KG		448x42x600mm (WxHxD) / 13.0KG	
Packing Dimensions / Gross weights	720x190x800mm (WxHxD) / 18.5KG		720x190x800mm (WxHxD) / 19.5KG	
<b>Accessory</b>				
1.8meter IEC Type Power Cord				
<b>Option Relate Item</b>				
CVU-018	1.8meter 2-in-1 KVM Cable-USB&VGA		CVU-030	3.0meter 2-in-1 KVM Cable-USB&VGA
CVU-050	5.0meter 2-in-1 KVM Cable-USB&VGA		DIP-101	KVM over IP module for Remote Bios Level Access