

# Matrix DB15 LCD Console Drawers

Optimize rack space. Maximize rack monitoring



The Anso range of LCD console drawers provides a variety of features that simplify to access servers to making system monitoring, troubleshooting and software upgrades.

The self-locking rails when in the fully extended open position and the ultra-convenient auto lock release when the LCD panel is closed, make for simple and hassle free operation.

17" or 19" A-Grade LCD panels, Matrix DB15 8 or 16 port KVM switch & one CAT6 remote console, available two option remote IP consoles.

Up to four Consoles, Provide multi-users simultaneous access.

## Optional Remote CAT6 Receiver

- Connecting by CAT6 cable, Remote console up to 300 meters,
- Pure hardware solution make network independent,
- No software required
- Dual user access at remote site.




## Optional Remote IP Access

- Two expansion slots allows you to add two optional KVM over IP module to enable remote access to your servers.
- Gain BIOS level access to your servers for system maintenance, support or failure recovery via secure SSL authentication and encryption.




## Features

- Support Combo interface, VGA-USB & VGA-PS/2.
- Multi-users simultaneous access, up to four consoles.
- Build in CAT6 console extension port up to 300 meters.
- Durable 104-key keyboard and touch pad.
- Quick and simple installation.
- Self-locking and auto release rails for ultra-convenience.
- Port selection via push buttons or On-Screen-Display (OSD).
- Dedicated daisy chain port to expand up to 240 servers.
- Access Control List (ACL) security function for up to 8 independent user accounts.



Rear of KVM-1708M/1908M-AST-M7



Rear of KVM-1716M/1916M-AST-M7

Part No.		KVM-1708M-AST-M7	KVM-1716M-AST-M7	KVM-1908M-AST-M7	KVM-1916M-AST-M7
Direct no. of Computers		8	16	8	16
Maximum no. of Computers		232 (Daisy Chain)	240 (Daisy Chain)	232 (Daisy Chain)	240 (Daisy Chain)
LCD	Size	17"		19"	
	Backlight	LED		LED	
	Resolution	1280*1024		1280*1024	
	Max.color	16.7M		16.7M	
	Luminance	250cd/m2		250cd/m2	
	View Angel (H/V)	176 / 170		170 / 160	
	Contrast Ratio	1000 : 1		1000 : 1	
Port Selection		Push Button, OSD or Hotkey			
Expansion Slot		Yes, option for Remote IP Access x 2			
Buildin remote console		Yes , for use with option CAT6 console receiver unit up to 300 meters			
KB/Mouse Emulation		USB			
Rack Depth		500mm to 1100mm ( rack cabinet front rails to rear rails )			
Power		100-240V AC 50/60Hz via IEC Type power cord			
Environment		Operation temp: 0 to 50°C Storage temp: -20 to 60°C Humidity: 10% - 90%, non-condensing Shock: 10G acceleration ( 11ms duration) Vibration: 17 to 500Hz 1G PTP			
Physical Dimensions / Net Weights		448x42x580mm (WxHxD) / 12.0KG		448x42x580mm (WxHxD) / 12.5KG	
Packing Dimensions / Gross weights		715x140x780mm (WxHxD) / 18.0KG		715x140x780mm (WxHxD) / 18.5KG	
<b>Accessory</b>					
1.8meter IEC Type Power Cord					
<b>Option Relate Item</b>					
CVU-018	1.8meter 2-in-1 KVM Cable-USB&VGA	CVP-018	1.8meter 3-in-1 KVM Cable-PS/2&VGA		
CVU-030	3.0meter 2-in-1 KVM Cable-USB&VGA	CVP-030	3.0meter 3-in-1 KVM Cable-PS/2&VGA		
CVU-050	5.0meter 2-in-1 KVM Cable-USB&VGA	CVP-050	5.0meter 3-in-1 KVM Cable-PS/2&VGA		
DIP-101	KVM over IP module for Remote Bios Level Access	DCC-300R	Remote CAT6 console receiver up to 300 meters		