

# Combo CAT6 LCD Console Drawers

Optimize rack space. Maximize rack monitoring



## Optional Remote IP Access

- An expansion slot allows you to add an optional KVM over IP module to enable remote access to your servers.
- Gain BIOS level access to your servers for system maintenance, support or failure recovery via secure SSL authentication and encryption.



## Features

- Support combo interface, VGA-USB & VGA-PS/2.
- Up to 40 meters between Servers to KVM.
- Durable 104-key keyboard and touch pad.
- Quick and simple installation.
- Self-locking and auto release rails for ultra-convenience.
- Port selection via push buttons or On-Screen-Display (OSD).
- Dedicated daisy chain port to expand up to 256 servers.
- Access Control List (ACL) security function for up to 8 independent user accounts.

The Anno range of LCD console drawers provides a variety of features that simplify to access servers to making system monitoring, troubleshooting and software upgrades.


The self-locking rails when in the fully extended open position and the ultra-convenient auto lock release when the LCD panel is closed, make for simple and hassle free operation.

Available with 17" or 19" A-Grade LCD panels, Combo CAT6 8, 16 or 32 port integrated KVM switch & with a remote IP console.


Using CAT5 or CAT6 ethernet cable, support max. Computer distance up to 40 meters away.



Rear of KVM-1708/1908ASL-M6



Rear of KVM-1716/1916ASL-M6



Rear of KVM-1732/1932ASL-M6

Part No.	KVM-1708ASL-M6	KVM-1716ASL-M6	KVM-1732ASL-M6	KVM-1908ASL-M6	KVM-1916ASL-M6	KVM-1932ASL-M6
Direct no. of Computers	8	16	32	8	16	32
Maximum no. of Computers	232(Daisy Chain)	240(Daisy chain)	256(Daisy chain)	232(Daisy Chain)	240(Daisy chain)	256(Daisy chain)
LCD	Size	17"		19"		
	Backlight	LED		LED		
	Resolution	1280*1024		1280*1024		
	Max. color	16.7M		16.7M		
	Luminance	250cd/m2		250cd/m2		
	View Angel (H/V)	176 / 170		170 / 160		
Contrast Ratio	1000 : 1		1000 : 1			
Port Selection	Push Button, OSD or Hotkey					
Expansion Slot	Yes, option for Remote IP Access					
Max. Computer Distance	40 meters ( Servers to KVM )					
KB/Mouse Emulation	USB & PS2					
Rack Depth	500mm to 1100mm ( rack cabinet front rails to rear rails )					
Power	100-240V AC 50/60Hz via IEC Type power cord					
Environment	Operation temp: 0 to 50°C Storage temp: -20 to 60°C Humidity: 10% - 90%, non-condensing Shock: 10G acceleration ( 11ms duration) Vibration: 17 to 500Hz 1G PTP					
Physical Dimensions / Net Weights	448x42x580mm (WxHxD) / 12.0KG			448x42x580mm (WxHxD) / 12.5KG		
Packing Dimensions / Gross weights	715x140x780mm (WxHxD) / 18.0KG			715x140x780mm (WxHxD) / 18.5KG		

### Accessory

1.8meter IEC Type Power Cord

### Option Relate Item

DGU	CAT6 KVM Dongle-USB&VGA	DGP	CAT6 KVM Dongle -PS/2&VGA
DGD	CAT6 KVM Dongle-USB&DVI	DIP-101	KVM over IP module for Remote Bios Level Access



China (Factory)  
Add : The south faces industry area of Xia Gang Fu Hai road, Chang'an Town, Dongguan City, Guangdong, China.  
Tel : +86-769-81666360, 81666395-97  
Fax : +86-769-81666306  
Email : sales@annso.com.tw

Taiwan (Head Quarter)  
Anno Technology Co., Ltd.  
NO.53, Ming YI Street, Luzhou Dist. New Taipei City, Taiwan  
Email : sales@annso.com.tw