

4K 8 ports HDMI LCD Console Drawers

Optimize rack space. Maximize rack monitoring




(USB Port for device access)



Features

- 17.3" 4K 3840 x 2160 resolution
- Support 1920 x 1080 & 1920 x 1200 resolution
- Support USB-HDMI interface.
- 8 ports HDMI 2.0 input
- Front 1x USB, Rear 1x USB 2.0 Type A, Sharing USB peripheral Device for computer (ex, flash disk, hard driver, KB/Mouse).
- Additional two USB console port to add local KB/Mouse.
- Build in 2x 2 watts stereo speakers.
- Durable 104-key keyboard and touch pad.
- Quick and simple installation.
- Self-locking and auto release rails for ultra convenience.
- Port selection via push buttons or hotkey.

HDMI LCD console drawers provide a variety of features that simplify to access servers to making system monitoring, troubleshooting and software upgrades. The self-locking rails when in the fully extended open position and the ultra convenient auto lock release when the LCD panel is closed, make for simple and hassle-free operation. Available with 17.3"4K A-Grade LCD panels, integrated 8 ports USB-HDMI KVM switch.



Rear of KVM-1708SWHD-M2-4K

| Part No. | | KVM-1708SWHD-M2-4K | |
|------------------------------------|---------------------|--|--------------------|
| Direct no. of Computers | | 8 | |
| Maximum no. of Computers | | 8 | |
| LCD | Size | 17.3" | |
| | Backlight | LED | |
| | Resolution | 4K resolution 3840 x 2160 | |
| | Max.color | 16.7M | |
| | Luminance | 400cd/m2 | |
| | View Angel (H/V) | 178 / 178 | |
| | Contrast Ratio | 1000 : 1 | |
| Port Selection | | Push Button, Hotkey | |
| USB Local console | | Yes , USB x2 for KB/ Mouse | |
| USB HUB | | 1x Front , 1xRear USB 2.0 Type A for Peripheral USB Device | |
| KB/Mouse Emulation | | USB | |
| Rack Depth | | 450mm to 650mm (rack cabinet front rails to rear rails) | |
| Power | | 100-240V AC 50/60Hz via IEC Type power cord | |
| Environment | | Operation temp: 0 to 50℃ Storage temp: -20 to 60℃ Humidity: 10% - 90%, non-condensing Shock: 10G acceleration (11ms duration) Vibration: 17 to 500Hz 1G PTP | |
| Physical Dimensions / Net Weights | | 443x42x457.2mm (WxHxD) /11KG | |
| Packing Dimensions / Gross weights | | 710x190x620mm (WxHxD) / 16.5KG | |
| Accessory | | | |
| 1.8meter IEC Type Power Cord | | | |
| Option Relate Item | | | |
| CH-018 | 1.8meter HDMI Cable | CU-018 | 1.8meter USB Cable |