

Combo DB15 LCD Console Drawers

Optimize rack space. Maximize rack monitoring

Ver. 2023-8-23



Optional Remote IP Access

- An expansion slot allows you to add an optional KVM over IP module to enable remote access to your servers.
- Gain BIOS level access to your servers for system maintenance, support or failure recovery via secure SSL authentication and encryption.



The Anso range of LCD console drawers provide a variety of features that simplify to access servers to making system monitoring, troubleshooting and software upgrades.

The self-locking rails when in the fully extended open position and the ultra-convenient auto lock release when the LCD panel is closed, make for simple and hassle-free operation.


Available with 17" or 19" A-Grade LCD panels, combo DB15 8 or 16 port integrated KVM switch & with an option remote IP console.

Features

- Support combo interface, VGA-USB & VGA-PS/2.
- Durable 104-key keyboard and touch pad.
- Quick and simple installation.
- Self-locking and auto release rails for ultra-convenience.
- Port selection via push buttons or On-Screen-Display (OSD).
- Dedicated daisy chain port to expand up to 240 servers.
- Access Control List (ACL) security function for up to 8 independent user accounts.



Rear of KVM-1708/1908AST-M6



Rear of KVM-1716/1916AST-M6

Part No.	KVM-1708AST-M6	KVM-1716AST-M6	KVM-1908AST-M6	KVM-1916AST-M6
Direct no. of Computers	8	16	8	16
Maximum no. of Computers	232(Daisy Chain)	240(Daisy chain)	232(Daisy Chain)	240(Daisy chain)
LCD	Size	17"		19"
	Backlight	LED		LED
	Resolution	1280*1024		1280*1024
	Max. color	16.7M		16.7M
	Luminance	250cd/m2		250cd/m2
	View Angel (H/V)	176 / 170		170 / 160
	Contrast Ratio	1000 : 1		1000 : 1
Port Selection	Push Button, OSD or Hotkey			
Expansion Slot	Yes, option for Remote IP Access			
KB/Mouse Emulation	USB & PS2			
Rack Depth	500mm to 1100mm (rack cabinet front rails to rear rails)			
Power	100-240V AC 50/60Hz via IEC Type power cord			
Environment	Operation temp: 0 to 50℃ Storage temp: -20 to 60℃ Humidity: 10% - 90%, non-condensing Shock: 10G acceleration (11ms duration) Vibration: 17 to 500Hz 1G PTP			
Physical Dimensions / Net Weights	448x42x580mm (WxHxD) / 12.0KG		448x42x580mm (WxHxD) / 12.5KG	
Packing Dimensions / Gross weights	715x140x780mm (WxHxD) / 18.0KG		715x140x780mm (WxHxD) / 18.5KG	
Accessory				
1.8meter IEC Type Power Cord				
Option Relate Item				
CVU-018	1.8meter 2-in-1 KVM Cable-USB&VGA	CVP-018	1.8meter 3-in-1 KVM Cable-PS/2&VGA	
CVU-030	3.0meter 2-in-1 KVM Cable-USB&VGA	CVP-030	3.0meter 3-in-1 KVM Cable-PS/2&VGA	
CVU-050	5.0meter 2-in-1 KVM Cable-USB&VGA	CVP-050	5.0meter 3-in-1 KVM Cable-PS/2&VGA	
DIP-101	KVM over IP module for Remote Bios Level Access			