

USB HUB DB15 LCD Console Drawers

Optimize rack space. Maximize rack monitoring

Ver. 2023-8-23



↑ (USB Port for device access)



The Anno range of LCD console drawers provide a variety of features that simplify to access servers to making system monitoring, troubleshooting and software upgrades.


The self-locking rails in the fully extended open position and the ultra convenient auto lock release when the LCD panel is closed, make for simple and hassle-free operation.

Available with 17" or 19" A-Grade LCD panels, combo DB15 8 ports integrated KVM switch & additional one USB local console.

Support USB HUB 2.0 and touch screen enable function.

Features

- Support USB interface, VGA-USB.
- Front 1x USB, Rear 2x USB 2.0 Type A, Sharing USB peripheral Device for computer (ex, flash disk, hard driver, KB/Mouse).
- Additional one USB Local console to add local KB/Mouse & VGA.
- Durable 104-key keyboard and touch pad.
- Quick and simple installation.
- Self-locking and auto release rails for ultra convenience.
- Port selection via push buttons or On-Screen-Display (OSD).



Rear of KVM-1708P/1908P-M6/ULC

Part No.		KVM-1708P-M6/ULC	KVM-1908P-M6/ULC
Direct no. of Computers		8	
Maximum no. of Computers		8	
LCD	Size	17"	19"
	Backlight	LED	LED
	Resolution	1280*1024	1280*1024
	Max. color	16.7M	16.7M
	Luminance	250cd/m2	250cd/m2
	View Angel (H/V)	176 / 170	170 / 160
Contrast Ratio		1000 : 1	
Port Selection		Push Button, OSD or Hotkey	
USB Local console		Yes, USB x2 for KB/ Mouse, VGA x1	
USB HUB		Yes, Front 1x USB 2.0 , Rear 2x USB 2.0 Type A for USB Peripheral Device	
Touch Screen		Yes, for option (Driver needed)	
KB/Mouse Emulation		USB	
Rack Depth		500mm to 1100mm (rack cabinet front rails to rear rails)	
Power		100-240V AC 50/60Hz via IEC Type power cord	
Environment		Operation temp: 0 to 50℃ Storage temp: -20 to 60℃ Humidity: 10% - 90%, non-condensing Shock: 10G acceleration (11ms duration) Vibration: 17 to 500Hz 1G PTP	
Physical Dimensions / Net Weights		448x42x600mm (WxHxD) / 12.5KG	448x42x600mm (WxHxD) / 13.0KG
Packing Dimensions / Gross weights		720x190x800mm (WxHxD) / 18.5KG	720x190x800mm (WxHxD) / 19.5KG
Accessory			
1.8meter IEC Type Power Cord			
Option Relate Item			
CVU-018	1.8meter 2-in-1 KVM Cable-USB&VGA	CVU-030	3.0meter 2-in-1 KVM Cable-USB&VGA
CVU-050	5.0meter 2-in-1 KVM Cable-USB&VGA		