

Combo DB15 LCD Console Drawers

Optimize rack space. Maximize rack monitoring

Ver. 2023-8-23




The Anno range of LCD console drawers provide a variety of features that simplify to access servers to making system monitoring, troubleshooting and software upgrades.

The self-locking rails when in the fully extended open position and the ultra-convenient auto lock release when the LCD panel is closed, make for simple and hassle-free operation.

Available with 17" or 19" A-Grade LCD panels, combo DB15 8 or 16 port integrated KVM switch & additional one USB local console.

Features

- Support combo interface, VGA-USB & VGA-PS/2.
- Additional one USB Local console to add local KB/Mouse & VGA.
- Durable 104-key keyboard and touch pad.
- Quick and simple installation.
- Self-locking and auto release rails for ultra-convenience.
- Port selection via push buttons or On-Screen-Display (OSD).
- Dedicated daisy chain port to expand up to 240 servers.



Rear of KVM-1708/1908AST-M6/ULC



Rear of KVM-1716/1916AST-M6/ULC

Part No.		KVM-1708AST-M6/ULC	KVM-1716AST-M6/ULC	KVM-1908AST-M6/ULC	KVM-1916AST-M6/ULC
Direct no. of Computers		8	16	8	16
Maximum no. of Computers		232(Daisy Chain)	240(Daisy chain)	232(Daisy Chain)	240(Daisy chain)
LCD	Size	17"		19"	
	Backlight	LED		LED	
	Resolution	1280*1024		1280*1024	
	Max. color	16.7M		16.7M	
	Luminance	250cd/m2		250cd/m2	
	View Angel (H/V)	176 / 170		170 / 160	
	Contrast Ratio	1000 : 1		1000 : 1	
Port Selection		Push Button, OSD or Hotkey			
USB Local console		Yes , USB x2 for KB/ Mouse , VGA x1			
KB/Mouse Emulation		USB & PS2			
Rack Depth		500mm to 1100mm (rack cabinet front rails to rear rails)			
Power		100-240V AC 50/60Hz via IEC Type power cord			
Environment		Operation temp: 0 to 50 °C Storage temp: -20 to 60 °C Humidity: 10% - 90%, non-condensing Shock: 10G acceleration (11ms duration) Vibration: 17 to 500Hz 1G PTP			
Physical Dimensions / Net Weights		448x42x580mm (WxHxD) / 12.0KG		448x42x580mm (WxHxD) / 12.5KG	
Packing Dimensions / Gross weights		715x185x780mm (WxHxD) / 18.0KG		715x185x780mm (WxHxD) / 18.5KG	
Accessory					
1.8meter IEC Type Power Cord					
Option Relate Item					
CVU-018	1.8meter 2-in-1 KVM Cable-USB&VGA	CVP-018	1.8meter 3-in-1 KVM Cable-PS/2&VGA		
CVU-030	3.0meter 2-in-1 KVM Cable-USB&VGA	CVP-030	3.0meter 3-in-1 KVM Cable-PS/2&VGA		
CVU-050	5.0meter 2-in-1 KVM Cable-USB&VGA	CVP-050	5.0meter 3-in-1 KVM Cable-PS/2&VGA		