

USB HUB DB15 LCD Console Drawers

Optimize rack space. Maximize rack monitoring

Ver. 2023-8-23



↑ (USB Port for device access)

The Anno range of LCD console drawers provide a variety of features that simplify to access servers to making system monitoring, troubleshooting and software upgrades.


The self-locking rails when in the fully extended open position and the ultra-convenient auto lock release when the LCD panel is closed, make for simple and hassle-free operation.

Available with 17" or 19" A-Grade LCD panels, combo DB15 8 ports integrated KVM switch & with an option remote IP console.

Support USB HUB 2.0 and touch screen enable function.


Optional Remote IP Access

- An expansion slot allows you to add an optional KVM over IP module to enable remote access to your servers.
- Gain BIOS level access to your servers for system maintenance, support or failure recovery via secure SSL authentication and encryption.



Features

- Support USB interface, VGA-USB.
- Front 1x USB, Rear 2x USB 2.0 Type A, Sharing USB peripheral Device for computer (ex, flash disk ,hard driver, KB/Mouse).
- Durable 104-key keyboard and touch pad.
- Quick and simple installation.
- Self-locking and auto release rails for ultra-convenience.
- Port selection via push buttons or On-Screen-Display (OSD).
- Access Control List (ACL) security function for up to 8 independent user accounts.



Rear of KVM-1708P/1908P-AST-M6

Part No.	KVM-1708P-AST-M6	KVM-1908P-AST-M6	
Direct no. of Computers	8		
Maximum no. of Computers	8		
LCD	Size	17"	
	Backlight	LED	
	Resolution	1280*1024	
	Max. color	16.7M	
	Luminance	250cd/m2	
	View Angel (H/V)	176 / 170	
	Contrast Ratio	1000 : 1	
Port Selection	Push Button, OSD or Hotkey		
Expansion Slot	Option for remote IP access		
USB HUB	Yes, Front 1x USB 2.0, Rear 2x USB 2.0 Type A for USB Peripheral Device		
Touch Screen	Yes, for option (Driver needed)		
KB/Mouse Emulation	USB		
Rack Depth	500mm to 1100mm (rack cabinet front rails to rear rails)		
Power	100-240V AC 50/60Hz via IEC Type power cord		
Environment	Operation temp: 0 to 50 °C Storage temp: -20 to 60 °C Humidity: 10% - 90%, non-condensing Shock: 10G acceleration (11ms duration) Vibration: 17 to 500Hz 1G PTP		
Physical Dimensions / Net Weights	448x42x600mm (WxHxD) / 12.5KG	448x42x600mm (WxHxD) / 13.0KG	
Packing Dimensions / Gross weights	720x190x800mm (WxHxD) / 18.5KG	720x190x800mm (WxHxD) / 19.5KG	
Accessory			
1.8meter IEC Type Power Cord			
Option Relate Item			
CVU-018	1.8meter 2-in-1 KVM Cable-USB&VGA	CVU-030	3.0meter 2-in-1 KVM Cable-USB&VGA
CVU-050	5.0meter 2-in-1 KVM Cable-USB&VGA	DIP-101	KVM over IP module for Remote Bios Level Access