

# Panel Mount Industrial Display Monitor (Small Size) Model # IPMB-065



## Features

- 6mm aluminum front bezel with hardness glass protect screen ( AR glass & touch for optional ).
- Front bezel NEMA4 / IP65 compliant.
- Front osd control buttons to optimized display.
- Build in 2x 2watts stereo speakers.
- Wide range DC 8-30V power input for option.
- Standard with VGA+ Audio or DVI-D+VGA+Audio input (Composite Video, BNC Loop in-out for option).
- Panel (Flush ) mount with clips.
- Meet standard VESA hole , support desk stand / wall mount / Swing Arm mounting.

## LCD Characteristics :

Screen Size	6.5"
Backlight Type	LED
Resolution	640x480
Contrast Ratio	600:1
Brightness ( cd/m2 )	700
View Angles ( H/V )	160/140
Pixel Size ( HxV ) mm	0.207x0.207
Max. Color	16.2M
MTBF ( Hrs. )	50,000

## Input Signals:

DVI-D(24Pin Connector, Female )	YES
VGA(15Pin Connector, Female )	YES
Audio(3.5" Jack)	YES
Power Input	DC 12V input via External AC adapter

## User Controls Interface:

Power ON / OFF via Front Button
Power Mode Status LED indicator
OSD ( On Screen Display ) Buttons

## Mechanical and Environmental:

IP Protect	Front IP65 Grade
Mounting	Panel ( Flush ) Mount with clips, VESA Mount
Construction	Aluminum Front Bezel + Metal Housing
Operating Temperature	0 - 50 deg. C
Operating Humidity	5% - 95% ( non -condensing )
Anti-Vibration	5 - 500 Hz / 1 Grms PTP
Anti-Shock	15G / Peak ( 11 ms )
Physical Dimension ( WxHxD )	201 x 165 x 48 ( mm )
Packing Dimension ( WxHxD )	305 x 230 x 200 ( mm )
Net Weight / Gross Weight	2 / 3.5 ( KGs )
Certification and Approvals	CE / FCC / RoHs

## Available Optional items:

Touch Screen	Resistive, Capacitive, SAW, IR Touch
AR Hardness Glass	3mm Anti-Reflective Protect Glass
Composite Video	RCA Phono Plug
BNC Loop in-out	Standard 75Ω BNC Connector
DC Power	wide range 8-30V DC Power

