

Panel Mount Industrial Display Monitor (Small Size) Model # IPMB-07



Features

- 6mm aluminum front bezel with hardness glass protect screen (AR glass & touch for optional).
- Front bezel NEMA4 / IP65 compliant.
- Osd control buttons to optimized display.
- Build in 2x 2watts stereo speakers.
- Wide range DC 8-30V power input for option.
- Standard with HDMI + VGA + Audio input (Composite Video for option).
- Panel (Flush) mount with clips.
- Meet standard VESA hole , support desk stand / wall mount / Swing Arm mounting.

LCD Characteristics :

Screen Size	7" wide
Backlight Type	LED
Resolution	1280x800
Contrast Ratio	800:1
Brightness (cd/m2)	350
View Angles (H/V)	170/170
Pixel Size (HxV) mm	0.117x0.117
Max. Color	262K
MTBF (Hrs.)	50,000

Input Signals:

HDMI	HDMI
VGA	D-SUB 15Pin Connector (Female)
Audio	3.5" Jack
Power Input	12V DC jack with hanger
Touch-USB (option)	USB A Type connector

User Controls Interface:

Power ON / OFF Button
Power Mode Status LED indicator
OSD (On Screen Display) Buttons

Power Specifications :

AC Power Input	External Power Adapter , 100-240V AC Input
Wide Range DC Power Input (option)	Screw Type Terminal Block with internal wide Range DC 8-30V power module

Mechanical and Environmental:

IP Protect	Front IP65 Grade
Mounting	Panel (Flush) Mount with clips, VESA Mount
Construction	Aluminum Front Bezel + Metal Housing
Operating Temperature	0 - 50 deg. C
Operating Humidity	5% - 95% (non -condensing)
Anti-Vibration	5 - 500 Hz / 1 Grms PTP
Anti-Shock	15G / Peak (11 ms)
Physical Dimension (WxHxD)	200 x 148 x 40 (mm)
Packing Dimension (WxHxD)	305 x 230 x 200 (mm)
Net Weight / Gross Weight	2 / 3.5 (KGs)
Certification and Approvals	CE / FCC / RoHS

Available Optional items:

Touch Screen	Resistive, Capacitive, SAW, IR Touch
AR Hardness Glass	3mm Anti-Reflective Protect Glass
Composite Video	RCA Phono Plug
DC Power	wide range 8-30V DC Power

