

Panel Mount Industrial Display Monitor (Small Size) Model # IPMB-08



Features

- 6mm aluminum front bezel with hardness glass protect screen (AR glass & touch for optional).
- Front bezel NEMA4 / IP65 compliant.
- Front osd control buttons to optimized display.
- Build in 2x 2watts stereo speakers.
- Wide range DC 8-30V power input for option.
- Standard with VGA+ Audio or DVI-D+VGA+Audio input (Composite Video, BNC Loop in-out for option).
- Panel (Flush) mount with clips.
- Meet standard VESA hole , support desk stand / wall mount / Swing Arm mounting.

LCD Characteristics :

Screen Size	8"
Backlight Type	LED
Resolution	1024x768
Contrast Ratio	700:1
Brightness (cd/m ²)	250
View Angles (H/V)	150/150
Pixel Size (HxV) mm	0.053x0.158
Max. Color	262K
MTBF (Hrs.)	50,000

Input Signals:

DVI-D(24Pin Connector, Female)	N/A
VGA(15Pin Connector, Female)	YES
Audio(3.5" Jack)	YES
Power Input	DC 12V input via External AC adapter

User Controls Interface:

Power ON / OFF via Front Button
Power Mode Status LED indicator
OSD (On Screen Display) Buttons

Mechanical and Environmental:

IP Protect	Front IP65 Grade
Mounting	Panel (Flush) Mount with clips, VESA Mount
Construction	Aluminum Front Bezel + Metal Housing
Operating Temperature	0 - 50 deg. C
Operating Humidity	5% - 95% (non -condensing)
Anti-Vibration	5 - 500 Hz / 1 Grms PTP
Anti-Shock	15G / Peak (11 ms)
Physical Dimension (WxHxD)	255 x 200 x 46 (mm)
Packing Dimension (WxHxD)	370 x 280 x 200 (mm)
Net Weight / Gross Weight	3 / 4.5 (KGs)
Certification and Approvals	CE / FCC / RoHs

Available Optional items:

Touch Screen	Resistive, Capacitive, SAW, IR Touch
AR Hardness Glass	3mm Anti-Reflective Protect Glass
Composite Video	RCA Phono Plug
BNC Loop in-out	Standard 75Ω BNC Connector
DC Power	wide range 8-30V DC Power

