

Combo DB15 LCD Console Drawers

Optimize rack space. Maximize rack monitoring

Ver. 2023-9-03



The Anso range of LCD console drawers provides a variety of features that simplify to access servers to making system monitoring, troubleshooting and software upgrades.

The self-locking rails when in the fully extended open position and the ultra convenient auto lock release when the LCD panel is closed, make for simple and hassle free operation.

Configure with 21.5 or 23.8 inch A-Grade FHD LCD panels, combo DB15 8 or 16 port integrated KVM switch & with an option remote IP console.


Optional Remote IP Access

- An expansion slot allows you to add an optional KVM over IP module to enable remote access to your servers.
- Gain BIOS level access to your servers for system maintenance, support or failure recovery via secure SSL authentication and encryption.



Features

- Support combo interface, GA-USB & VGA-PS/2.
- Durable 104-key keyboard and touch pad.
- Quick and simple installation.
- Self-locking and auto release rails for ultra convenience.
- Port selection via push buttons or On-Screen-Display (OSD).
- Dedicated daisy chain port to expand up to 240 servers.
- Access Control List (ACL) security function for up to 8 independent user accounts.



Rear of KVM-2108AST-M2
Rear of KVM-2408AST-M2



Rear of KVM-2116AST-M2
Rear of KVM-2416AST-M2

Part No.	KVM-2108AST-M2	KVM-2116AST-M2	KVM-2408AST-M2	KVM-2416AST-M2
Direct no. of Computers	8	16	8	16
Maximum no. of Computers	232(Daisy Chain)	240(Daisy chain)	232(Daisy Chain)	240(Daisy chain)
LCD	Size	21.5"	23.8"	
	Backlight	LED		LED
	Resolution	1920*1080 FULL HD (up to 1920*1200)		1920*1080 FULL HD (up to 1920*1200)
	Max.color	16.7M		16.7M
	Luminance	250cd/m2		250cd/m2
	View Angel (H/V)	178 / 178		178 / 178
Contrast Ratio	3000 : 1		1000 : 1	
Port Selection	Push Button, OSD or Hotkey			
Expansion Slot	Yes, option for Remote IP Access			
KB/Mouse Emulation	USB & PS2			
Rack Depth	500mm to 1100mm (rack cabinet front rails to rear rails)			
Power	100-240V AC 50/60Hz via IEC Type power cord			
Environment	Operation temp: 0 to 50°C			
	Storage temp: -20 to 60°C			
	Humidity: 10% - 90%, non-condensing			
	Shock: 10G acceleration (11ms duration) Vibration: 17 to 500Hz 1G PTP			
Physical Dimensions / Net Weights	448x42x775mm / 18.5 KG		448x42x775mm / 19.5 KGs	
Packing Dimensions / Gross weights	730x260x880mm / 24 KG		730x260x880mm / 25 KGs	
Accessory				
1.8meter IEC Type Power Cord				
Option Relate Item				
CVU-018	1.8meter 2-in-1 KVM Cable-USB&VGA	CVP-018	1.8meter 3-in-1 KVM Cable-PS/2&VGA	
CVU-030	3.0meter 2-in-1 KVM Cable-USB&VGA	CVP-030	3.0meter 3-in-1 KVM Cable-PS/2&VGA	
CVU-050	5.0meter 2-in-1 KVM Cable-USB&VGA	CVP-050	5.0meter 3-in-1 KVM Cable-PS/2&VGA	
DIP-101	KVM over IP module for Remote Bios Level Access			