

Combo DB15 LCD Console Drawers

Optimize rack space. Maximize rack monitoring

Ver. 2023-9-03




The Anno range of LCD console drawers provides a variety of features that simplify to access servers to making system monitoring, troubleshooting and software upgrades.

The self-locking rails when in the fully extended open position and the ultra convenient auto lock release when the LCD panel is closed, make for simple and hassle free operation.

Configure with 21.5 or 23.8 inch A-Grade FHD LCD panels, combo DB15 8 or 16 port integrated KVM switch & additional one USB local console.

Features

- Support combo interface, VGA-USB & VGA-PS/2.
- Additional one USB Local console to add local KB/Mouse & VGA.
- Durable 104-key keyboard and touch pad.
- Quick and simple installation.
- Self-locking and auto release rails for ultra convenience.
- Port selection via push buttons or On-Screen-Display (OSD).
- Dedicated daisy chain port to expand up to 240 servers.



Rear of KVM-2108AST-M2/ULC
Rear of KVM-2408AST-M2/ULC



Rear of KVM-2116AST-M2/ULC
Rear of KVM-2416AST-M2/ULC

Part No.		KVM-2108AST-M2/ULC	KVM-2116AST-M2/ULC	KVM-2408AST-M2/ULC	KVM-2416AST-M2/ULC
Direct no. of Computers		8	16	8	16
Maximum no. of Computers		232(Daisy Chain)	240(Daisy chain)	232(Daisy Chain)	240(Daisy chain)
LCD	Size	21.5"		23.8"	
	Backlight	LED		LED	
	Resolution	1920*1080 FULL HD (support up to 1920*1200)		1920*1080 FULL HD (support up to 1920*1200)	
	Max.color	16.7M		16.7M	
	Luminance	250cd/m2		250cd/m2	
	View Angel (H/V)	178 / 178		178 / 178	
	Contrast Ratio	3000 : 1		1000 : 1	
Port Selection		Push Button, OSD or Hotkey			
USB Local console		Yes , USB x2 for KB/ Mouse , VGA x1			
KB/Mouse Emulation		USB & PS2			
Rack Depth		500mm to 1100mm (rack cabinet front rails to rear rails)			
Power		100-240V AC 50/60Hz via IEC Type power cord			
Environment		Operation temp: 0 to 50°C Storage temp: -20 to 60°C Humidity: 10% - 90%, non-condensing Shock: 10G acceleration (11ms duration) Vibration: 17 to 500Hz 1G PTP			
Physical Dimensions / Net Weights		448x42x775mm / 18.5 KG		448x42x775mm / 19.5 KGs	
Packing Dimensions / Gross weights		730x260x880mm / 24 KG		730x260x880mm / 25 KGs	
Accessory					
1.8meter IEC Type Power Cord					
Option Relate Item					
CVU-018	1.8meter 2-in-1 KVM Cable-USB&VGA	CVP-018	1.8meter 3-in-1 KVM Cable-PS/2&VGA		
CVU-030	3.0meter 2-in-1 KVM Cable-USB&VGA	CVP-030	3.0meter 3-in-1 KVM Cable-PS/2&VGA		
CVU-050	5.0meter 2-in-1 KVM Cable-USB&VGA	CVP-050	5.0meter 3-in-1 KVM Cable-PS/2&VGA		