



# Military Grade Rack Mount Industrial Display Monitor

## Model # RMB-17W-MIL



### Features

- Meet MIL-STD-810F standard
- Compact 19 inch rack mountable with 7U height
- Industrial Grade 17.3" LCD panel, support 1920 x 1080 resolution
- Support up to 1920 x 1200 resolution
- DVI-D, VGA, Audio input
- 90 ° tilt adjustment while mounted in rack: 45° ~-45° ( V )
- Aluminum chassis with hardness glass protect screen
- Front bezel NEMA4 / IP65 compliant
- Front osd control buttons to optimized display
- Build in 2x 2watts stereo speakers

### LCD Characteristics :

Screen Size	17.3"
Backlight Type	LED
Resolution	1920*1080 Full HD ( support resolution up to 1920x1200 )
Contrast Ratio	650:1
Brightness ( cd/m2 )	300 (high brightness for option, up to 1000 nits)
View Angles ( H/V )	140/120
Pixel Size ( HxV ) mm	0.1989x 0.1989
Max. Color	262K

### Input Signals:

DVI-D	DVI-D 24Pin Connector (Female)
VGA	D-SUB 15Pin Connector (Female)
Audio	3.5" Jack
Power Input	MIL lock connector, 100-240V AC Input

### Power Specifications :

AC Power Input	MIL lock connector, 100-240V AC Input
Wide Range DC Power Input ( option )	MIL lock connector with internal wide Range DC 9-36V power module

### User Controls Interface:

Power ON / OFF via Front Buttons
Power Mode Status LED indicator
OSD ( On Screen Display ) Button

### Mechanical and Environment (MIL-STD-810F):

Height	7U	
IP Protect	Front bezel NEMA4 / IP65 compliant	
Mounting	Rack Mount and VESA Mount	
Construction	Aluminum Housing	
Operating Temperature	0 ~ 70 deg. C	Method 501.5 and 502.5
Storing Temperature	-30 ~ 75 deg. C	Method 501.5 and 502.5
Operating Humidity	5% - 95%, non -condensing	Method 507.5
Anti-Vibration	5 - 500 Hz / 1 Grms PTP	Method 514.6
Anti-Shock	15G / Peak (11 ms)	Method 516.6
Physical Dimension (WxHxD)	482 x 310 (7U) x 62 (mm)	
Packing Dimension (WxHxD)	610 x 400 x 210(mm)	
Net Weight / Gross Weight	5.5 / 6.5 (KGs)	
Certification and Approvals	CE / FCC / RoHS	

