

Combo DB15 LCD Console Drawers

Optimize rack space. Maximize rack monitoring

Short Depth Version

Ver. 2023-9-03



The Anno range of LCD console drawers provides a variety of features that simplify access to servers for making system monitoring, troubleshooting and software upgrades.

The self-locking rails when in the fully extended open position and the ultra-convenient auto lock release when the LCD panel is closed, make for simple and hassle free operation.


Available with 15" or 17" A-Grade LCD panels, combo DB15 8 or 16 port integrated KVM switch.

Features

- Support combo interface, VGA-USB & VGA-PS/2.
- Short depth design suit for mobile rack and limited space.
- Durable 104-key keyboard and touch pad.
- Quick and simple installation.
- Self-locking and auto release rails for ultra-convenience.
- Port selection via push buttons or On-Screen-Display (OSD).
- Dedicated daisy chain port to expand up to 240 servers.



Rear of KVM-1508S/1708S-AST-M2



Rear of KVM-1516S/1716SAST-M2

Part No.	KVM-1508S-AST-M2	KVM-1516S-AST-M2	KVM-1708S-AST-M2	KVM-1716S-AST-M2
Direct no. of Computers	8	16	8	16
Maximum no. of Computers	232(Daisy Chain)	240(Daisy chain)	232(Daisy Chain)	240(Daisy chain)
LCD	Size	15"		17"
	Backlight		LED	LED
	Resolution		1024*768	1280*1024
	Max.color		16.7M	16.7M
	Luminance		450cd/m2	250cd/m2
	View Angel (H/V)		160 / 140	176 / 170
	Contrast Ratio		700 : 1	1000 : 1
Port Selection	Push Button, OSD or Hotkey			
USB Local console / Expansion Slot	N/A			
KB/Mouse Emulation	USB & PS2			
Rack Depth	380mm to 620mm (rack cabinet front rails to rear rails)		450mm to 650mm (rack cabinet front rails to rear rails)	
Power	100-240V AC 50/60Hz via IEC Type power cord			
Environment	Operation temp: 0 to 50°C Storage temp: -20 to 60°C Humidity: 10% - 90%, non-condensing Shock: 10G acceleration (11ms duration) Vibration: 17 to 500Hz 1G PTP			
Physical Dimensions / Net Weights	443x42x406.4mm (WxHxD) /12.5KG		443x42x457.2mm (WxHxD) /14KG	
Packing Dimensions / Gross weights	715x140x600mm (WxHxD) / 15.5KG		715x140x600mm (WxHxD) /17KG	
Accessory				
1.8meter IEC Type Power Cord				
Option Relate Item				
CVU-018	1.8meter 2-in-1 KVM Cable-USB&VGA	CVP-018	1.8meter 3-in-1 KVM Cable-PS/2&VGA	
CVU-030	3.0meter 2-in-1 KVM Cable-USB&VGA	CVP-030	3.0meter 3-in-1 KVM Cable-PS/2&VGA	
CVU-050	5.0meter 2-in-1 KVM Cable-USB&VGA	CVP-050	5.0meter 3-in-1 KVM Cable-PS/2&VGA	