

Combo DB15 LCD Console Drawers

Optimize rack space. Maximize rack monitoring

Small Screen version



The Annso range of LCD console drawers provides a variety of features that simplify to access servers to making system monitoring, troubleshooting and software upgrades.

Push & pull out LCD module, make for simple and hassle free operation.

Cost efficient for space limited, Integrated 8" A-Grade LCD panels, combo DB15, 8 or 16 port KVM switch & with an option remote IP console.


Optional Remote IP Access

- An expansion slot allows you to add an optional KVM over IP module to enable remote access to your servers.
- Gain BIOS level access to your servers for system maintenance, support or failure recovery via secure SSL authentication and encryption.



Features

- Support combo interface, VGA-USB & VGA-PS/2.
- Durable 80-key keyboard and touch pad.
- Cost efficient and Short depth design suit for mobile rack and limited space.
- Quick and simple installation.
- Self-locking and auto release rails for ultra-convenience.
- Port selection via push buttons or On-Screen-Display (OSD).
- Dedicated daisy chain port to expand up to 240 servers.
- Access Control List (ACL) security function for up to 8 independent user accounts.



Rear of KVM-0808-AST



Rear of KVM-0816-AST

Part No.	KVM-0808-AST	KVM-0816-AST	
Direct no. of Computers	8	16	
Maximum no. of Computers	232(Daisy Chain)	240(Daisy chain)	
LCD	Size	8"	
	Backlight	LED	
	Resolution	1024*768	
	Max.color	262K	
	Luminance	250cd/m2	
	View Angel (H/V)	150 / 150	
Contrast Ratio	700 : 1		
Port Selection	Push Button, OSD or Hotkey		
Expansion Slot	Yes, option for Remote IP Access		
KB/Mouse Emulation	USB & PS2		
Rack Depth	380mm to 650mm (rack cabinet front rails to rear rails)		
Power	100-240V AC 50/60Hz via IEC Type power cord		
Environment	Operation temp: 0 to 50 °C Storage temp: -20 to 60 °C Humidity: 10% - 90%, non-condensing Shock: 10G acceleration (11ms duration) Vibration: 17 to 500Hz 1G PTP		
Physical Dimensions / Net Weights	448.5x43.6x381mm (WxHxD) / 6.5kg	448.5x43.6x381mm (WxHxD) / 7kg	
Packing Dimensions / Gross	600x195x515mm (WxHxD) / 9.5kg	600x195x515mm (WxHxD) / 10kg	
Accessory			
1.8meter IEC Type Power Cord			
Option Relate Item			
CVU-018	1.8meter 2-in-1 KVM Cable-USB&VGA	CVP-018	1.8meter 3-in-1 KVM Cable-PS/2&VGA
CVU-030	3.0meter 2-in-1 KVM Cable-USB&VGA	CVP-030	3.0meter 3-in-1 KVM Cable-PS/2&VGA
CVU-050	5.0meter 2-in-1 KVM Cable-USB&VGA	CVP-050	5.0meter 3-in-1 KVM Cable-PS/2&VGA
DIP-101	KVM over IP module for Remote Bios Level Access		