Combo DB15 LCD Console Drawers

Optimize rack space. Maximize rack monitoring Waterproof Version Ver. 2023-9-03



The Annso range of LCD console drawers provides a variety of features that simplify to access servers to making system monitoring, troubleshooting and software upgrades.

The self-locking rails when in the fully extended open position and the ultraconvenient auto lock release when the LCD panel is closed, make for simple and hassle free operation.

Available with $17^{\prime\prime\prime}$ A-Grade LCD panels, combo DB15 8 or 16 port integrated KVM switch.

LCD module front face compliant with IP65 waterproof grade, keyboard and touch pad module IP68 grade for tough environment application.



Features

- Support combo interface, VGA-USB & VGA-PS2.
- Short depth design suit for mobile rack and limited space.
- LCD front face IP65 waterproof grade.
- Silicon 98-key keyboard and touch pad IP68 waterproof grade.
- Quick and simple installation.
- Self-locking and auto release rails for ultra-convenience.
- Port selection via push buttons or On-Screen-Display (OSD).
- Dedicated daisy chain port to expand up to 240 servers.





Rear of KVM-1708S-AST-M2-IP

Rear of KVM-1716S-AST-M2-IP

Part No.		KVM-1708S-AST-M2-IP		KVM-1716S-AST-M2-IP	
Direct no. of Computers		8		16	
Maximum no. of Computers		232(Daisy Chain)		240(Daisy chain)	
	Size	17"			
LCD	Backlight	LED			
	Resolution	1280*1024			
	Max.color	16.7M			
	Luminance	250cd/m2			
	View Angel (H/V)	176 / 170			
	Contrast Ratio	1000:1			
Port Selection		Push Button, OSD or Hotkey			
USB Local console / Expansion Slot		N/A			
KB/Mouse Emulation		USB & PS2			
Rack Depth		450mm to 650mm (rack cabinet front rails to rear rails)			
Power		100-240V AC 50/60Hz via IEC Type power cord			
Environment		Operation temp: 0 to 50 °C			
		Storage temp: -20 to 60 ℃ Humidity: 10% - 90%, non-condensing			
		Shock: 10G acceleration (11ms duration)			
		Vibration: 17 to 500Hz 1G PTP			
Physical Dimensions / Net Weights		443x42x457.2mm (WxHxD) /14KG			
Packing Dimensions / Gross weights		605x168x700mm (WxHxD) /17KG			
Accessory					
1.8meter IEC	Type Power Cord				
Option Relate Item					
CVU-018	1.8meter 2-in-1 KV	M Cable-USB&VGA CVP-01	8	1.8meter 3-in-1 KVM Cable-PS/2&VGA	
CVU-030 3.0meter 2-in-1 KV		M Cable-USB&VGA CVP-03	0	3.0meter 3-in-1 KVM Cable-PS/2&VGA	
CVU-050	5.0meter 2-in-1 KV	M Cable-USB&VGA CVP-05	0	5.0meter 3-in-1 KVM Cable-PS/2&VGA	



China (Factory)

Add: The south faces industry area of Xia Gang Fu Hai road, Chang'an Town, Dongguan City, Guangdong, China.

Tel: +86-769-81666360, 81666395-97

Fax: +86-769-81666306 Email: sales@annso.com.tw Taiwan (Head Quarter) Annso Technology Co., Ltd. NO.53, Ming YI Street, Luzhou Dist. New

Taipei City, Taiwan

Email: sales@annso.com.tw